

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
25 January 2007 (25.01.2007)

PCT

(10) International Publication Number  
**WO 2007/009253 A1**

(51) International Patent Classification:

*H04L 29/02* (2006.01)      *H04Q 7/22* (2006.01)  
*H04L 7/00* (2006.01)      *H04L 12/16* (2006.01)

712 Willow Wood P1, Waterloo, Ontario N2T 2T7 (CA).  
**KALOUGINA, Tatiana** [CA/CA]; 124 Keats Way P1,  
Waterloo, Ontario N2L 5H3 (CA).

(21) International Application Number:

PCT/CA2006/001201

(74) Agents: **PERRY, Stephen, J.** et al.; PERRY + PART-  
NERS, 1300 Yonge Street, Suite 500, Toronto, Ontario  
M4T 1X3 (CA).

(22) International Filing Date: 21 July 2006 (21.07.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2,513,022      22 July 2005 (22.07.2005)      CA


(71) Applicant (for all designated States except US): **RE-  
SEARCH IN MOTION LIMITED** [CA/CA]; 295  
Phillip Street, Waterloo, Ontario N2L 3W8 (CA).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP,  
KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT,  
LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA,  
NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC,  
SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ,  
UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR COMMUNICATING STATE MANAGEMENT BETWEEN A BROWSER USER-AGENT AND A SERVER



(57) Abstract: A method for communicating state information between a server and a mobile device browser, comprising the steps of providing a control channel between the server and mobile device browser, transmitting at least one message from the mobile device browser to the server over the control channel indicative of browsing-related cache data, and regulating subsequent transmission of data from the server to the mobile device browser based on the at least one message.

WO 2007/009253 A1



FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,  
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

## **System and Method for Communicating State Management between a Browser User-Agent and a Server**

### **Field**

**[0001]** This specification relates generally to mobile data communication systems, and more particularly to a method for communicating state information between a server, such as a proxy server, and a mobile Internet browser.

### **Background**

**[0002]** Mobile communication devices are becoming increasingly popular for business and personal use due to a relatively recent increase in number of services and features that the devices and mobile infrastructures support. Handheld mobile communication devices, sometimes referred to as mobile stations, are essentially portable computers having wireless capability, and come in various forms. These include Personal Digital Assistants (PDAs), cellular phones and smart phones.

**[0003]** It is known in the art to provide Internet browser functionality in such mobile communication devices. In operation, a browser user-agent in the handheld mobile communication device issues commands to an enterprise or proxy server implementing a Mobile Data Service (MDS), which functions as an acceleration server for browsing the Internet and transmitting text and images to the mobile device for display. Such enterprise or proxy servers generally do not store the state of their clients (i.e. the browser user-agent), or if they do, the state that is stored is minimal and limited to HTTP state (i.e. cookies). Typically, such enterprise or proxy servers fetch and transmit data to the browser user-agent when the browser makes a data request. In order to improve the performance of the browser on the mobile device, some enterprise or proxy servers fetch all the data required in order to fulfill the data request from the browser, aggregate the fetched data, and transmit the data to the device browser. For instance, if a HyperText Markup Language (HTML) page is requested, the enterprise or proxy server fetches any additional files referenced within the HTML page (e.g. Images, inline CSS code, JavaScript, etc.). Since the proxy server fetches all the additional files within the HTML file, the device does not have to make additional data requests to retrieve these additional files. Although this methodology is faster than having the device make multiple requests, the proxy server nonetheless has to send all of the data again if the site is later revisited. This is because the proxy server has no knowledge of the device caches (e.g. caches that are saved in persistent memory, for different types of data such as a content cache to store raw data that is cached as a result of normal browser activity, a channel cache containing data

that is sent to the device by a channel or cache push, and a cookie cache containing cookies that are assigned to the browser by visited Web pages). For example, if a user browses to CNN.com, closes the browser to perform some other function (e.g. place a telephone call or access e-mail messages, etc.) and then later accesses the CNN.com Web site (or follows a link from CNN.com to a news story), the banner "CNN.com" will be transmitted from the MDS to the device browser each time the site is accessed, thereby consuming significant bandwidth, introducing delay, etc.

**[0004]** It is known in the art to provide local file caching. One approach is set forth in *GloMop: Global Mobile Computing By Proxy*, published September 13, 1995, by the GloMop Group, wherein PC Card hard drives are used as portable file caches for storing, as an example, all of the users' email and Web caches. The user synchronizes the file caches and the proxy server keeps track of the contents. Mobile applications (clients) are able to check the file caches before asking for information from the proxy server by having the server verify that the local version of a given file is current.

### **Summary**

**[0005]** In general, there is provided a method for communicating state information between a server and a mobile device browser, comprising providing a control channel between the server and mobile device browser, transmitting over the control channel at least one message from the mobile device browser to the server indicative of browsing-related state data, and regulating subsequent transmission of data from the server to the mobile device browser based on the at least one message.

**[0006]** According to an exemplary embodiment, an HTTP-like protocol is set forth, referred to herein as the Browser Session Management (BSM) protocol, for providing the aforementioned control channel between the proxy server and the mobile device browser, so that the mobile device browser can communicate to the proxy server what data the mobile device browser has cached (from previous browsing). The BSM protocol is an "out of band" protocol in that BSM communications are in addition to the usual stream of HTTP requests from the mobile device browser to the proxy server and provides "metadata" relating to cache contents. This metadata is used by the proxy server when handling subsequent requests from the mobile device browser, to determine what data to send to the mobile device browser, thereby significantly reducing data transfer on subsequent requests relative to the prior art methodology discussed above.

**[0007]** Because the proxy server is aware of what the mobile device browser has stored in its cache, the amount of data sent to the mobile device browser may be reduced, thereby increasing the performance of the mobile device browser and reducing operational cost. For example, if after the first request the CNN.com banner is cached and if the proxy server "knows" that the information has been cached then there will be no need to send the CNN.com banner to the mobile device browser upon subsequent visits to the CNN web site.

**[0008]** In contrast to the prior art *GloMop* caching methodology discussed above, the exemplary method set forth herein synchronizes the cache contents when the mobile device browser connects to the proxy server in order to initiate a session and keeps track of changes to the cache via knowledge of what data has been sent to the mobile device browser in combination with state information periodically received from the mobile device browser identifying what has actually been cached. Also, as set forth in greater detail below, the proxy server uses this cache knowledge to determine what to send back to the mobile device browser. In contrast, the prior art *GloMop* methodology does not contemplate sending any state information to the proxy server for identifying what has actually been cached in the device. Moreover, the prior art *GloMop* approach first checks the local cache, and then queries the proxy server to determine whether a particular data item in the cache is current or not. According to the *GloMop* prior art, the proxy server does not use its own knowledge of the mobile device browser cache to determine what to send back to the mobile device browser.

**[0009]** Additional aspects and advantages will be apparent to a person of ordinary skill in the art, residing in the details of construction and operation as more fully hereinafter described and claimed, reference being had to the accompanying drawings.

#### **Brief Description of the Drawings**

**[0010]** A detailed description of the preferred embodiment is set forth in detail below, with reference to the following drawings, in which:

**[0011]** Figure 1 is a block diagram of a communication system for implementing Internet browsing functionality in a mobile communication device;

**[0012]** Figure 2A shows communication protocol stacks for the communication system of Figure 1;

**[0013]** Figure 2B shows communication protocol stacks for a Browser Session Management (BSM) protocol according to an exemplary embodiment;

**[0014]** Figure 3 is a flowchart showing the method for communicating information between a proxy server and a mobile Internet browser, according to the preferred embodiment; and

**[0015]** Figure 4 is a flowchart of an exemplary method according to the present specification.

#### **Detailed Description**

**[0016]** Figure 1 depicts the architecture of a system for providing wireless e-mail and data communication between a mobile device 1 and an enterprise or proxy server 9. Communication with the device 1 is effected over a wireless network 3, which in turn is connected to the Internet 5 and proxy server 9 through corporate firewall 7 and relay 8. Alternatively, the device 1 can connect directly (via the Internet) through the corporate firewall 7 to the proxy server 9. When a new message is received in a user's mailbox within email server 11, enterprise or proxy server 9 is notified of the new message and email application 10 (e.g. Messaging Application Programming Interface (MAPI), MS Exchange, etc.) copies the message out to the device 1 using a push-based operation. Alternatively, an exemplary architecture for proxy server 9 may provide a browsing proxy but no email application 10. Indeed, the exemplary embodiment set forth herein relates to mobile browser device functionality and is not related to email functionality. Proxy server 9 also provides access to data on an application server 13 and the Web server 15 via a Mobile Data Service (MDS) 12. Additional details regarding e-mail messaging, MAPI sessions, attachment service, etc., are omitted from this description as they are not germane. Nonetheless, such details would be known to persons of ordinary skill in the art.

**[0017]** In terms of Web browsing functionality, the device 1 communicates with enterprise or proxy server 9 using HTTP over an IP protocol optimized for mobile environments. In some embodiments, the device 1 communicates with the proxy server 9 using HTTP over TCP/IP, over a variant of TCP/IP optimized for mobile use (e.g. Wireless Profiled TCP), or over other, proprietary protocols. For example, according to the communications protocol of Figure 2A, HTTP is run over Internet Point-to-Point Protocol (IPPP) and an encrypted Global Messaging Exchange (GME) channel over which datagrams are exchanged to transport data between the device 1 and proxy server 9. The GME datagrams are 64Kbit in size whereas the wireless network 3 can only transport UDP datagrams with payloads up to 1500 bytes. Therefore, a Message Delivery Protocol (MDP) is used to separate the GME datagrams into one or more MDP packets, each of which is less than 1500 bytes (default size 1300 bytes), which are transported over UDP/IP to and from the relay 8 which, in turn communicates with the proxy

server 9 via Server Relay Protocol (SRP)/TCP/IP. The MDP protocol includes acknowledgements, timeouts and re-sends to ensure that all packets of the GME datagram are received.

**[0018]** The communication between the device 1 and proxy server 9 is optionally encrypted with an encryption scheme, such as Triple Data Encryption Algorithm (TDEA, formerly referred to as Triple Data Encryption Standard (Triple DES)), as is known in the art. The proxy server 9 enables Internet access, preprocesses and compresses HTML and XML content from the Web server 15 before sending it to the device 1, transcodes content type, stores HTTP cookies on behalf of the device 1, and supports certificate authority authentications, etc.

**[0019]** In response to a request from the device browser, the proxy server 9 retrieves content from Web server 15 and creates a custom document containing both images to be displayed on the device and data in the form of compressed versions of requested portions of the document. The document is preferably of "multi-part" format to improve transmission to and processing efficiency within the device 1. Specifically, in order to display composite Web pages (i.e. pages composed of a main WML or HTML page and one or more related auxiliary files, such as style sheets, JavaScript files, or image files) the device browser is normally required to send multiple HTTP requests to the proxy server 9. However, according to the multi-part generation feature, the proxy server 9 posts all necessary parts of a composite Web page in a single bundle, enabling the browser to download all the required content with a single request. The header in the server response identifies the content as a multi-part bundle (e.g. Multi-Purpose Mail Extensions (MIME)/multipart, as defined by RFC 2112, E. Levinson, March 1997).

**[0020]** In order to indicate device browser state information to the proxy server 9, three transitional state messages are defined herein, as follows: CONNECT, UPDATE and DISCONNECT, each of which conforms to the exemplary BSM protocol. As shown in Figure 2B, the BSM communications protocol is identical to the protocol of Figure 2A except that the conventional HTTP layer of the protocol stack is replaced by an HTTP-like BSM layer.

**[0021]** The CONNECT transitional message creates a new session with a connection identifier carried in the payload, device information and state data (e.g. current cache and device information) in the form of a set of hash functions for use by the proxy server 9 in preparing a response. Specific care is taken not to identify to the proxy server 9 what cookies or cache entries are contained on the device 1. Only hash values of the state data are sent to the proxy server 9 in order to protect the identity of state data on the device 1.

**[0022]** The CONNECT message also contains a unique authentication key for generating a MAC (Message Authentication Code) using a Hash Message Authentication Code (HMAC) algorithm that incorporates a cryptographic hash function in combination with the authentication key. Each portion of a multi-part document from the proxy server 9 also contains an HMAC, generated using the authentication key, that is used for authenticating the proxy server 9 before adding that portion to the device cache. This prevents a third party from creating its own multi-part document and sending it to the device 1 for injecting cache entries that could be used to extract personal information from the user.

**[0023]** Upon receipt of the CONNECT message, the proxy server 9 uses the state information to regulate or control the transmission of content retrieved from Web server 15 (step 23) to the device 1. One example of an application where this information can be used is when the proxy server 9 is pre-fetching images, inline Cascading Style Sheets (CSS), JavaScript, and the like for an HTML document. If the proxy server 9 already knows that the device 1 has the image, inline CSS, or JavaScript document, there is no need for resending the documents.

**[0024]** The UPDATE transition message notifies the proxy server 9 of changes that have occurred on the device 1 since the last CONNECT message or the last UPDATE message, between the device 1 and proxy server 9 (e.g. new cache entries added because of a push, or invoking the "Low Memory Manager" (LMM) or other memory-space preservation policies on the device and purging items from the cache).

**[0025]** The DISCONNECT transition message notifies the proxy server 9 that the device 1 will no longer send any more messages using the connection identifier specified in the payload. The proxy server 9 can then de-allocate any memory reserved for the connect session between the device 1 and proxy server 9. Upon receiving the disconnect message, the proxy server 9 deletes any session cookies for the device 1 (if it is processing cookies) along with state information. Receiving a request on the identified connection after the DISCONNECT has been received, and before any subsequent CONNECT message has been received, is defined as an error.

**[0026]** Since state is indicated from the device 1 to the proxy server 9, and state may be stored in transient memory within proxy server 9, a mechanism is provided for the proxy server 9 to return to the device 1 a message indicating that the session the device is trying to use is not valid. Once this occurs, the device 1 issues a new CONNECT message and establishes a new session with the proxy server 9, and re-issues the original request.



**[0027]** The data protocol set forth herein is similar to HTTP in order to reduce complexity and to reuse code that already exists for the HTTP protocol. Thus, data transmission according to this protocol begins with a STATE keyword; followed by a BSM (Browser Session Management) protocol identifier and a "Content-Length" header. The end of the "headers" is indicated by a double CRLF (a sequence of control characters consisting of a carriage return (CR) and a line feed (LF)), much like HTTP. After the double CRLF pair (i.e. \r\n) a WBXML (WAP Binary Extensible Markup Language) encoded document is inserted as the message payload. The WBXML document is later decoded using a DTD (Document Type Definition) and codebook, as discussed in greater detail below. The indication of the protocol version refers to what version of the DTD to validate the request against (ie. BSM/1.1 stipulates using version 1.1 of the DTD). It should be noted that WBXML encoding of the contents of BSM messages is set forth to allow for more efficient processing of the BSM message at the device 1, but that in alternate embodiments, the BSM message may be formatted as normal (textual) XML.

**[0028]** The following is an example communication using the protocol according to the preferred embodiment:

```
CONNECT BSM/1.0\r\n
Content-Length: 40\r\n
\r\n
<WBXML Encoded document of length 40 bytes>

BSM/1.0 200\r\n
\r\n
```

**[0029]** In the foregoing, the first four lines form the CONNECT message from the device 1 to the proxy server 9, and the last two lines are the response from the proxy server 9.

**[0030]** An exemplary XML document, is as follows:

```
<?xml version="1.0"?>
<!DOCTYPE bsm PUBLIC "-// DTD BSM 1.0//EN"
    "http://www.something.com/go/mobile/BSM/bsm_1.0.xml">
<bsm id="2" hmac="12345678901234567890">
<cache>
<size>123012</size>
<entry urlHash="FEEDDEED01" dataHash="FDDEDEED11" etag="SomeEtag"
expiry="256712323"/>
</cache>
<device>
<version>4.0.1.123</version>
<memfree>12342342</memfree>
</device>
</bsm>
```

**[0031]** In the example, the state data includes the URL of an HTML page within the device

cache. It will be noted that the XML document payload includes a connection identifier (i.e. bsm id="2"), a value indicating when the document was last modified (i.e. etag="SomeEtag"), a page expiry (i.e. expiry="256712323"), and hash values for a URL (i.e. entry urlHash="FEEDDEED01") and a data attribute (i.e. entry dataHash="FDDEDEED11") rather than transmitting the actual URL and data attribute themselves. Thus, as shown in Figure 3, the hashes of the URL and data attribute of the cached page are sent to the proxy server 9 in the CONNECT string (step 21). The proxy server 9 then fetches the requested page from Web server 13 (step 23), computes hashes of device browser state data (step 25) and data from the Web server 13 (step 27), and compares the hashes of the URL and data attribute of the requested page with the hashed URL and data attribute of the cached page, and also compares the time stamps/expiration information (step 29) in order to determine whether the cached page is current. Specifically, in response to the proxy server 9 retrieving a portion from the Web server 13, it computes the dataHash and urlHash of that portion and performs a comparison to the dataHashes and urlHashes of the entries it has saved. There are three cases.

**[0032]** In the first case, if both the dataHash and the urlHash of the retrieved portion match the dataHash and urlHash of a cache entry that the proxy server 9 knows the device 1 has, then the server 13 simply omits this portion from the response, as the device 1 still has a valid entry in its cache.

**[0033]** In the second case, if the dataHash of the retrieved portion matches the dataHash of a cache entry that the proxy server 9 knows the device 1 has, but the urlHash of the retrieved portion does not match the urlHash of that cache entry, the server 13 inlines this updated portion in the combined response to the device 1. However, because the dataHash matches a dataHash of an entry that already exists on the device 1, the inlined response does not include the actual data, but instead only includes a new HTTP header whose value is the new dataHash. When the device 1 receives this inlined portion, it detects the special header, looks for the cache entry with that dataHash, and either creates or updates its cache entry for that URL with the data corresponding to the dataHash by copying that data from the other cache entry (the cache for device 1 is modified to have two indexes, one to retrieve cache entries by URL, the other to retrieve cache entries by dataHash). Finally, if the proxy server 9 already has a cache entry for the urlHash, it updates that entry with the new dataHash; otherwise it creates a new entry for this portion.

**[0034]** In the third case, if the dataHash of the retrieved portion does not match the dataHash of any of the cache entries that the proxy server 9 has received from the device 1 in

the BSM messages, then the server inlines the entire portion (headers and new data), since this portion has been updated and the device 1 does not contain the updated value anywhere in its cache.

**[0035]** Although not indicated in Figure 3, it will be appreciated that each inline part to be added to a document to be displayed at the device 1 is fetched. If the response code from the proxy server indicates a "304" (step 31), then the part (i.e., the "304" response) is written as a block in the multipart document. On the other hand, if the proxy server 9 returns a "200" (step 33), then the hash compare operation is performed, and the portion is only included in the multipart document if the hash compare function indicates it is not already on the device 1.

**[0036]** An exemplary DTD, according to the preferred embodiment, is as follows:

```
<!ELEMENT bsm (cache?, device)>
<!ATTLIST bsm
      id          NMTOKEN          #REQUIRED
>
<!ELEMENT cache (size, (entry)+)>
<!ATTLIST cache
      action      (add|remove|remove_all|quick_add)  "add"
>

<!ELEMENT entry EMPTY>
<!ATTLIST entry
      urlHash      CDATA          #REQUIRED
      dataHash     CDATA          #REQUIRED
      etag         CDATA          #IMPLIED
      expiry       NMTOKEN        #IMPLIED
      size         NMTOKEN        #IMPLIED
      last-modified NMTOKEN        #IMPLIED
>
<!ELEMENT size (#PCDATA)>
<!ELEMENT device (version, memfree)>
<!ELEMENT version (#PCDATA)>
<!ELEMENT memfree (#PCDATA)>
<!ELEMENT hmac (#PCDATA)>
```

Element/Code  
HMAC 12

Attribute/Code  
size 9 (instead of action)  
lastModified 10  
actionAdd 11  
actionRemove 12  
actionRemoveAll 13  
actionQuickAdd 14

**[0037]** Finally, an exemplary codebook, is as follows:

Element	Code
Session	5
Cache	6
Size	7
Entry	8
Device	9
Version	10
MemFree	11
HMAC	12

Attribute	Code
Id	5
UrlHash	6
dataHash	7
ETag	8
Expiry	9
Action	10

**[0038]** As is well known in the art, the codebook is used as a transformation for compressing the XML document to WBXML, wherein each text token is represented by a single byte from the codebook.

**[0039]** As discussed above, the proxy server 9 transmits multi-part documents in a proprietary format of compressed HTML, interspersed with data for images and other auxiliary files (which may or may not be related to the main HTML Web page). However, in a departure from conventional HTML, each document part may also include a response code (e.g. "200" for OK, or "304" for "not modified" to indicate that the specified document part has already been cached in the device 1). This may be used for selective downloading of document parts rather than entire documents and for indicating when a part (e.g. image) is about to expire. This is useful, for example, when one Web page links to another page containing one or more common elements.

**[0040]** Of course, certain device requests (e.g. page refresh) will always result in a full document download, irrespective of device state information stored in the proxy server 9.

**[0041]** It is contemplated that the inclusion of response codes may be used by heuristic processes within the proxy server 9 to learn user behaviour and modify downloading of documents based on tracking the history of certain changes reflected in the hash value (e.g. the server 9 may learn to download a certain page (e.g. CNN news) at a particular time each day

based the user's history of issuing requests for that page at regular times. As discussed above, because the downloaded documents are multi-part and contain embedded response codes, only those portions of the document that have changed are actually downloaded.

**[0042]** Figure 4 illustrates a broad aspect of the exemplary method, wherein a control channel is established between the mobile device 1 and proxy server 9 (step 41). The mobile device 1 then sends a message, over the control channel, that contains browser-related state data (step 43). The proxy server 9 thereafter regulates transmission of data to the mobile device 1 based on the state data received from the mobile device browser 1 (step 45). The method then ends (step 47).

**[0043]** As indicated above, the protocol of the preferred embodiment is preferably carried over a proprietary IPPP transport layer, but can also be easily adapted to run over TCP/IP on a specific port. The protocol is preferably implemented as a handler in the proxy server 9, thereby simplifying any currently existing protocol. (e.g. to avoid overloading a current HTTP protocol).

**[0044]** A person skilled in the art, having read this description of the preferred embodiment, may conceive of variations and alternative embodiments. For example, the conditional transfer of data based on communication of state information, as set forth above, may also be applied to separately transmitting individual portions of the multipart document as opposed to transmitting the entire document at once.

**[0045]** In some embodiments, the proxy server 9 uses heuristic algorithms to learn what additional data requests the device may make based on knowledge of the current request, and knowledge of past activity. In some instances, the device may follow a pattern of requesting a first Web page, and then a second Web page. For example, the device may first request the "cnn.com" Web page, and then request the "cnn.com/news" Web page. The proxy server 9 learns this pattern, and whenever the device requests the first Web page, the proxy server 9 determines that the device is likely to then request the second Web page. The proxy server 9 then fetches the second Web page, and uses its knowledge of the data cached on the device 1 (i.e. from the state information transferred to the proxy server 9 during initiation of the present connection) to determine whether the second Web page already exists within the data cached on the device. If so, the proxy server 9 includes information about the second Web page via response codes embedded within the response provided for the first Web page. If the device 1 requires the second Web page, then the device 1 can reference its cache and can avoid having to make a request to the proxy server 9 for the second Web page.

**[0046]** In other embodiments, heuristic processes within the proxy server 9 learn user behaviour and modify downloading of documents based on tracking the history of certain changes reflected in the hash value (e.g. the proxy server 9 may learn to download a certain page (e.g. CNN news) at a particular time each day based the user's history of issuing requests for that page at regular times). As discussed, because the downloaded documents are multi-part and contain embedded response codes, only those portions of the document that have changed are actually downloaded.

**[0047]** All such variations and alternative embodiments are believed to be within the ambit of the claims appended hereto.

What is claimed is:

1. A method for communicating state information between a server and a mobile device browser, comprising:
  - providing a control channel between the server and mobile device browser;
  - transmitting over said control channel at least one message from the mobile device browser to the server indicative of browsing-related state data; and
  - regulating subsequent transmission of data from the server to the mobile device browser based on said at least one message.
2. The method of claim 1, wherein said at least one message conforms to an out-of-band protocol and indicates said browsing-related state data to the server as a hash value.
3. The method of claim 2, wherein said protocol includes a transitional state message with payload including said hash value and a connection identifier, for notifying the server of current state information for a current session between the mobile device browser and the server.
4. The method of claim 3, wherein said protocol includes a transitional state message for notifying the server of changes in state subsequent to said current session between the mobile device browser and the server.
5. The method of claim 3, wherein said protocol includes a transitional state message for notifying the server that the mobile device browser has ceased sending messages using said connection identifier, in response to which the server de-allocates stored memory for the session.
6. The method of claim 5, wherein data transmission according to said protocol comprises, in sequence: a header representing said transitional state message; a protocol identifier and a Content-Length header; a sequence of control characters, and an XML-encoded document containing said hash value, a connection identifier and state information.
7. The method of claim 1, wherein each said subsequent transmission of data from the server contains a message authentication code (MAC) for authentication by the device prior to caching said data within the device.

8. A method for synchronizing cache contents of a mobile browser with a proxy server, comprising:
  - initiating a session between said browser and proxy server, including transmission of browser state information regarding said cache contents to said proxy server;
  - maintaining a record of data sent from the proxy server to the browser for storage in said cache;
  - maintaining a record of said state information regarding said cache contents transmitted from the browser to said proxy server; and
  - transmitting data requests from said browser to said proxy server, in response to which said proxy server accesses each said record of data and returns only data that do not already form part of said cache contents.
9. The method of claim 8, wherein said session conforms to an out-of-band protocol and indicates said browser state information to the proxy server as a hash value.
10. The method of claim 9, wherein said protocol includes a transitional state message with payload including said hash value and a connection identifier, for notifying the proxy server of current state information for a current session between said browser and the proxy server.
11. The method of claim 10, wherein said protocol includes a transitional state message for notifying the proxy server of changes in state subsequent to said current session between said browser and the proxy server.
12. The method of claim 10, wherein said protocol includes a transitional state message for notifying the proxy server that the browser has ceased sending messages using said connection identifier, in response to which the proxy server de-allocates stored memory for the session.
13. The method of claim 12, wherein data transmission according to said protocol comprises, in sequence: a header representing said transitional state message, a protocol identifier and a Content-Length header; a sequence of control characters, and an XML-encoded document containing said hash value, a connection identifier and state information.
14. The method of claim 8, wherein each said subsequent transmission of data from the



proxy server contains an encryption key for authentication by the browser prior to caching data.

15. A method of controlling delivery of content from an origin server to a mobile device browser via a proxy server, comprising:

transmitting state information from the mobile device browser to the proxy server indicative of cached content and associated expiry headers;  
retrieving data from said origin server to said proxy server responsive to a request from said mobile device browser; and

forwarding said data from said proxy server to said mobile device browser only in the event that said state information indicates that said mobile device has not already cached said data and otherwise indicating to said mobile device browser that said data is already cached and transmitting new expiry headers to the mobile device browser whereupon the browser performs a cache update with said new expiry headers.

16. The method of claim 15, wherein forwarding of said data from said proxy server to said mobile device browser further includes computing a hash value of said state information, computing a hash value of said data, comparing said hash values, forwarding said data from said proxy server to said mobile device browser in the event that said hash values are different, and sending a response to said mobile device browser containing a reference to data already cached in said mobile device browser.

17. A communication system, comprising:

a mobile device browser for transmitting over a control channel at least one message;  
and  
a server for receiving said at least one message and in response regulating transmission of data to the mobile device browser.

18. The communication system of claim 17, wherein said at least one message conforms to an out-of-band protocol and indicates said browsing-related state data to the server as a hash value.

19. A communication system, comprising:

an origin server storing data;  
a mobile device browser for transmitting state information indicative of cached content

and associated expiry headers; and

a proxy server for receiving said state information, retrieving said data from said origin server to said proxy server, and forwarding said data to said mobile device browser only in the event that said state information indicates that said mobile device has not already cached said data and otherwise indicating to said mobile device browser that said data is already cached and transmitting new expiry headers to the mobile device browser whereupon the browser performs a cache update with said new expiry headers.




Figure 1




Figure 2A




Figure 2B




Figure 3




Figure 4

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/CA2006/001201

## A. CLASSIFICATION OF SUBJECT MATTER

IPC: *H04L 29/02* (2006.01) , *H04L 7/00* (2006.01) , *H04Q 7/22* (2006.01) , *H04L 12/16* (2006.01)  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC: H04L, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic database(s) consulted during the international search (name of database(s) and, where practicable, search terms used)

Databases: Delphion and US West Patent Database

Keywords: server, state information, mobile, browser, control, transmit, regulate, message

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/0050062 A1 (CHEN et al.) 13 March 2003 (13-03-2003) abstract column 7, paragraph 0098 column 9, claim 16	1, 17
Y		2, 7, 18
Y	US 6,795,555 B1 (PARISIEN et al.) 21 September 2004 (21-09-2004) column 2, lines 38-42	2, 18
Y	US 2002/0031135 A1 (INOUE) 14 March 2002 (14-03-2002) page 5, paragraph 0064	7
A	US 5,825,890 (ELGAMAL et al.) 20 October 1998 (20-10-1998) see whole document	1-7, 17-18
A	US 2004/0223508 A1 (SAWYER et al.) 11 November 2004 see whole document	1-7, 17-18

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

1 December 2006 (01-12-2006)

Date of mailing of the international search report

15 December 2006 (15-12-2006)

Name and mailing address of the ISA/CA  
Canadian Intellectual Property Office  
Place du Portage I, C114 - 1st Floor, Box PCT  
50 Victoria Street  
Gatineau, Quebec K1A 0C9  
Facsimile No.: 001(819)953-2476

Authorized officer

Dennis Atkinson 819- 953-0816

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/CA2006/001201

## Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of the first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons :

1. ☐ Claim Nos. :  
because they relate to subject matter not required to be searched by this Authority, namely :
  
2. ☐ Claim Nos. :  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically :
  
3. ☐ Claim Nos. :  
because they are dependant claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows :

Claims 1-7 and 17-18 are directed to a method and system for communicating state information between a server and a mobile device browser.

Claims 8-14 are directed to a method for synchronizing cache contents of a mobile browser with a proxy server.

Claims 15-16 and 19 are directed to a method and system for controlling delivery of content from an origin server to a mobile device browser via a proxy server.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claim Nos. :
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim Nos. : 1-7 and 17-18

**Remark on Protest** ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

☐ No protest accompanied the payment of additional search fees.



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/CA2006/001201

Patent Document Cited in Search Report	Publication Date	Patent Family Member(s)	Publication Date
US2003050062	13-03-2003	CA2400848 A1	07-03-2003
US6795555	21-09-2004	CA2324094 A1 EP1122930 A2	30-06-2001 08-08-2001
US2002031135		EP1189411 A2 JP2002094558 A US6925087 B2 US2005237970 A1	20-03-2002 29-03-2002 02-08-2005 27-10-2005
US5825890	20-10-1998	US5657390 A	12-08-1997
US2004223508	11-11-2004	US6765925 B1	20-07-2004